# **QUESTIONS & ANSWERS**

Kill your exam at first Attempt





**IBM** 

C4040-332

High Availability for AIX - Technical Support and Administration -v2







- C. Halt the node on which application stop script has failed.
- D. Force shutdown all nodes in the cluster for data integrity.

#### **Answer:** C

### **QUESTION:** 123

A customer notices the following event in hacmp.out.

EVENT START: cluster\_notify NODE1 1 Sep 15 00:01:53 NOTIFY COMMAND:/usr/es/sbin/cluster/utilities/clissuepage NODE1 clverify has detected cluster configuration errors on node NODE1.

Why did this event occur?

- A. Automatic error notification has detected a cluster error and notified the dstrmgrES.
- B. Cluster verification has been initiated by the administrator and errors have been logged to hacmp.out.
- C. Automatic cluster verification has been configured and an error was detected with the cluster configuration.
- D. Notification has been sent that the cluster test tool automated procedure completed and has been logged in hacmp.out.

### **Answer:** C

# **QUESTION:** 124

Which fileset must be installed to enable message authentication and encryption?

- A. rsct.crypt
- B. rsct.core.sec
- C. cluster.es.cfs
- D. cluster.es.crypt

# **Answer:** A

# **QUESTION:** 125

A 2-node cluster has startup monitoring. The Action on Application failure of monitoring is set to "notify." The startup policy of the cluster is "Online on Home Node Only." The home node is Node1. Node 2 is up. If startup monitoring detects a failure during Node 1 startup, what will the state of the resource group be?

A. ERROR Node1 ONLINE Node2 B. ERROR Node1 OFFLINE Node2 C. OFFLINE Node1 ONLINE Node2 D. OFFLINENode1 OFFLINE Node2

#### **Answer:** C

# **QUESTION: 126**

A shared volume group (VG) was created in a PowerHA 7 environment. Given the following example, what must be changed in the VG definition?

```
root@lpar101[/]#
VOLUME GROUP:
VG STATE:
                              Isvg datavg0°
datavg01
                                                                                                                00c08bb600004c00000001367e2d80fb
16 megabyte(s)
639 (10224 megabytes)
627 (10032 megabytes)
12 (192 megabytes)
2 (Enabled)
                                                                                   VG IDENTIFIER:
PP SIZE:
                                                                                    TOTAL PPs:
FREE PPs:
G PERMISSION:
                                     read/write
                                                                                    VG DESCRIPTORS:
                                                                                    AUTO ON:
                                                                                                                 no
                                     1016
LTG size (Dynamic):
HOT SPARE:
PV RESTRICTION:
root@lpar101[/]#
                                    256 kilobyte(s)
                                                                                                                 no
                                                                                                                 non-relocatable
                                                                                    INFINITE RETRY: no
```

A. Set QUORUM to 1(Disabled).

- B. Set BB POLICY torelocatable.
- C. Set concurrent capable to enhanced concurrent.
- D. Set hot spare characteristics to yes(one to one).

# **Answer:** C

# **QUESTION:** 127

Complete the following statement:

With a cluster using EtherChannel backup for high availability of network interfaces, the netmon.cf file setting is not needed for local network failure detection if EtherChannel backup has \_\_\_\_\_\_:

- A. address to ping attribute
- B. multiple EtherChannel devices
- C. alternate EtherChannel address
- D. enabled automatic recovery afterfailover

#### **Answer:** A

### **QUESTION:** 128

The db\_group resource group become unmanaged after cluster service on node1 is forced down. Which action will change the state of db\_group resource group from unmanaged to Online on node2?

- A. Bring db\_group Onlinedirectly on node2
- B. Move resource group db\_group from node1 to node2
- C. Bring db\_group offline and then bring db\_group Online on node2
- D. Run clchres utility to change the state of db\_group resource to Online on node2

#### **Answer: C**

### **QUESTION:** 129

An administrator has written a custom verification method script and wants it distributed to all nodes in the cluster during cluster synchronization.

Which file collection should be changed to "Propagate files during cluster synchronization?"

- A. HACMP Cust
- B. HACMP\_Files
- C. HACMP Events
- D. Configuration\_Files

#### **Answer:** B

#### **QUESTION:** 130

After changing a PowerHA 6 cluster to reflect new IP addresses, an administrator attempts to synchronize a cluster and receives the following message:

cldare: A communication error prevents obtaining the VRMF from remote nodes.

A DARE cannot be run until this is corrected. Please ensure clcomd is running.

How can the administrator correct this error?

- A. Include the new IP addresses in /.rhosts on all cluster nodes.
- B. Include the new IP addresses in /etc/hosts.equiv on all cluster nodes.
- C. Include the new IP addresses in /usr/es/sbin/cluster/etc/rhosts on all cluster nodes.
- D. Include the new IP addresses in /usr/es/sbin/cluster/etc/clhosts on all cluster nodes.

#### **Answer:** C

### **QUESTION: 131**

A new application is added to the cluster and verification produces an error. What is the most likely reason?

- A. The application is running on one of the cluster nodes.
- B. Some application dependencies are missing from one or morenodes in the resource group.

- C. The application start script is not executable on one of the nodes in the resource group.
- D. The size of the application start script is not the same on all of the nodes in the resource group.

**Answer:** C

KILL EXAMS

KILLEXAMS.COM

# For More exams visit https://killexams.com/vendors-exam-list

